

## DIMENSIONS AND WEIGHTS TABLE

Nominal Outside Diameter			Wall Thickness		Weights		Schedules				
ND	mm	Inch	Inch	mm	Kg/m	lb/ft					
40	48,3		0,109	2,77	3,11	2,09	<b>10</b>				
			0,145	3,68	4,05	2,72		<b>STD 40</b>			
			0,200	5,10	5,43	3,65		<b>XS 80</b>			
50	60,3	2	0,109	2,77	3,93	2,64	<b>10</b>				
			0,110	2,80	3,97	2,67					
			0,126	3,20	4,51	3,03					
			0,142	3,60	5,03	3,38					
			0,154	3,90	5,42	3,64		<b>STD 40</b>			
			0,217	5,50	7,43	4,99		<b>XS 80</b>			
65	73,0		0,120	3,05	5,26	3,54	<b>10</b>				
			0,126	3,20	5,51	3,70					
			0,142	3,60	6,16	4,14					
			0,154	3,90	6,65	4,47					
			0,205	5,20	8,69	5,84		<b>STD 40</b>			
			0,276	7,00	11,39	7,66		<b>XS 80</b>			
80	88,9	3	0,110	2,80	5,95	3,99	<b>10</b>				
			0,126	3,20	6,76	4,54					
			0,142	3,60	7,57	5,09					
			0,157	4,00	8,37	5,63					
			0,189	4,80	9,95	6,69					
			0,217	5,50	11,31	7,60		<b>STD 40</b>			
			0,299	7,60	15,24	10,24		<b>XS 80</b>			
			100	114,3	4	0,126		3,20	8,77	5,89	<b>10</b>
0,142	3,60	9,83				6,60					
0,157	4,00	10,88				7,31					
0,189	4,80	12,96				8,71					
0,205	5,20	13,99				9,40					
0,220	5,60	15,01				10,09					
0,237	6,02	16,07				10,80	<b>STD 40</b>				
0,339	8,60	22,42				15,06	<b>XS 80</b>				
125	141,3	5				0,126	3,20	10,90	7,24	<b>10</b>	
						0,142	3,60	12,22	8,21		
			0,157	4,00	13,54	8,99					
			0,189	4,80	16,16	10,73					
			0,220	5,60	18,74	12,44					
			0,260	6,60	21,92	14,73	<b>STD 40</b>				
			0,280	7,10	23,50	15,60					
			0,374	9,50	30,88	20,75	<b>XS 80</b>				
150	168,3	6	0,142	3,60	14,62	9,82	<b>10</b>				
			0,157	4,00	16,21	10,89					

Nominal Outside Diameter			Wall Thickness		Weights		Schedules				
ND	mm	Inch	Inch	mm	Kg/m	lb/ft					
150	168,3	6	0,189	4,80	19,35	13,00	<b>10</b>				
			0,220	5,60	22,47	15,10					
			0,252	6,40	25,55	17,17					
			0,280	7,10	28,22	18,97		<b>STD 40</b>			
			0,311	7,90	31,25	21,00					
			0,433	11,00	42,67	22,00		<b>XS 80</b>			
			0,500	12,70	48,73	32,75					
			200	219,1	8	0,157		4,00	21,22	14,26	<b>10</b>
0,189	4,80	25,37				17,04					
0,205	5,20	27,43				18,43					
0,220	5,60	29,48				19,81					
0,252	6,40	33,57				22,56					
0,276	7,00	36,61				24,60					
0,311	7,90	41,14				27,65					
0,323	8,20	42,65				28,66	<b>STD 40</b>				
0,343	8,70	45,14				30,33					
0,437	11,10	56,94				38,26					
0,500	12,70	64,64				43,44	<b>XS 80</b>				
0,594	15,10	75,96				51,04	<b>100</b>				
250	273,1	10				0,157	4,00	26,54	17,84	<b>10</b>	
						0,189	4,80	31,76	21,34		
			0,220	5,60	36,94	24,82					
			0,252	6,40	42,09	28,28					
			0,280	7,10	46,57	31,29					
			0,307	7,80	51,03	34,29					
			0,343	8,70	56,72	38,12					
			0,366	9,30	60,50	40,65	<b>STD 40</b>				
			0,437	11,10	71,72	48,19					
			0,500	12,70	81,55	54,80	<b>XS 60</b>				
300	323,9	12	0,189	4,80	37,77	25,38	<b>10</b>				
			0,220	5,60	43,96	29,54					
			0,232	5,90	46,27	31,09					
			0,252	6,40	50,11	33,67					
			0,280	7,10	55,47	37,27					
			0,311	7,90	61,56	41,37					
			0,331	8,40	65,35	43,92					
			0,343	8,70	67,62	45,44					
			0,374	9,50	73,65	49,49		<b>STD 40</b>			
			0,406	10,30	79,65	53,52		<b>40</b>			

## DIMENSIONS AND WEIGHTS TABLE

Nominal Outside Diameter			Wall Thickness		Weights		Schedules					
ND	mm	Inch	Inch	mm	Kg/m	lb/ft						
300	323,9	12	0,437	11,10	85,62	57,53	<b>10</b>					
			0,469	11,90	91,56	61,52						
			0,500	12,70	97,46	65,49		<b>XS</b>				
			0,563	14,30	109,18	73,36		<b>60</b>				
			350	355,6	14	0,220		5,60	48,33	32,48	<b>10</b>	
						0,252		6,40	55,11	37,03		
0,280	7,10	61,02				41,00						
0,311	7,90	67,74				45,52						
0,343	8,70	74,42				50,01						
0,374	9,50	81,08				54,48	<b>STD 30</b>					
0,406	10,30	87,71				58,94						
0,437	11,10	94,30				63,37	<b>40</b>					
0,469	11,90	100,86				67,77						
0,500	12,70	107,39				72,16	<b>XS</b>					
400	406,4	16	0,220	5,60	55,35	37,19	<b>10</b>					
			0,248	6,30	62,16	41,77						
			0,280	7,10	69,91	46,98						
			0,311	7,90	77,63	52,17						
			0,343	8,70	85,32	57,33						
			0,374	9,50	92,98	62,48		<b>STD 30</b>				
			0,406	10,30	100,61	67,61						
			0,437	11,10	108,20	72,71						
			0,469	11,90	115,77	77,79						
			0,500	12,70	123,30	82,85		<b>XS 40</b>				
450	457,0	18	0,563	14,30	138,27	92,91	<b>60</b>					
			0,657	16,70	160,49	107,84						
			450	457,0	18	0,252		6,40	71,12	47,79	<b>10</b>	
						0,280		7,10	78,77	52,93		
						0,311		7,90	87,49	58,79		
						0,343		8,70	96,18	64,63		
						0,374		9,50	104,84	70,45		<b>STD</b>
						0,406		10,30	113,46	76,24		
0,437	11,10	122,05				82,02						
0,469	11,90	130,62				87,77						
0,500	12,70	139,15				93,50	<b>XS</b>					
0,563	14,30	156,11				104,90	<b>40</b>					
450	457,0	18	0,579	14,70	160,33	107,74	<b>40</b>					
			0,626	15,90	172,95	116,22						
			0,689	17,50	189,67	127,45						
			0,752	19,10	206,25	138,60		<b>60</b>				

Nominal Outside Diameter			Wall Thickness		Weights		Schedules				
ND	mm	Inch	Inch	mm	Kg/m	lb/ft					
500	508,0	20	0,252	6,40	79,16	53,20	<b>10</b>				
			0,311	7,90	97,43	65,47					
			0,343	8,70	107,12	71,98					
			0,374	9,50	116,78	78,47		<b>STD 20</b>			
			0,406	10,30	126,41	84,95					
			0,437	11,10	136,01	91,40					
			0,469	11,90	145,58	97,83					
			0,500	12,70	155,12	104,24		<b>XS 30</b>			
500	508,0	20	0,563	14,30	174,10	116,99	<b>40</b>				
			0,594	15,10	183,54	123,33					
			0,626	15,90	192,95	129,66					
			0,705	17,90	216,34	145,37					
			0,752	19,10	230,27	154,74					
			550	559,0	22	0,252		6,40	87,21	58,60	<b>10</b>
						0,280		7,10	96,63	64,93	
						0,311		7,90	107,36	72,14	
0,343	8,70	118,06				79,33					
0,374	9,50	128,73				86,50	<b>STD 20</b>				
0,406	10,30	139,37				93,65					
0,437	11,10	149,97				100,78					
0,469	11,90	160,55				107,88					
550	559,0	22	0,500	12,70	171,09	114,97	<b>XS 30</b>				
			0,563	14,30	192,08	129,07					
			0,626	15,90	212,95	143,09					
			0,689	17,50	233,68	157,03					
			0,752	19,10	254,30	170,88					
			0,811	20,60	273,51	183,79					
			600	610,0	24	0,252		6,40	95,26	64,01	<b>10</b>
						0,280		7,10	105,56	70,93	
0,343	8,70	129,00				86,69					
0,374	9,50	140,68				94,53	<b>STD 20</b>				
0,406	10,30	152,32				102,36					
0,437	11,10	163,93				110,16					
0,469	11,90	175,51				117,94					
0,500	12,70	187,06				125,70	<b>XS</b>				
600	610,0	24	0,563	14,30	210,07	141,16	<b>30</b>				
			0,626	15,90	232,94	156,53					
			0,689	17,50	255,69	171,82					
			0,752	19,10	278,32	187,02					
			0,811	20,60	299,41	201,20		<b>40</b>			